

HAIRDRYER INCLUDING A IONIZING DEVICE

BACKGROUND OF THE INVENTION

5 The present invention relates to a hairdryer including a ionizing device.

As is known, upon brushing or combing, air is electrostatically charged.

10 This electrostatic charge causes some drawbacks, such as a great difficulty in holding hair in a proper arrangement and preventing it from accumulating powder and impurity.

15 It has been found that negative ions tend to reduce or fully overcome the above mentioned problems.

Moreover, said ions, upon drying hair, greatly reduce the size of the water drops, thereby facilitating the processing of hair, since it is affected by an uneven moisture degree.

20 Thus, ion emitting hairdryers have already proposed, operating based on the above mentioned operating principle, but including different constructional means for generating ions.

25 Actually, prior ionic hairdryers included ionizing devices designed for providing weak ion emissions, generated by a mechanic piezoelectric system.

30 Further prior ionic hairdryers provided to use electronic ion generators or sources which, however, because of their comparatively large sizes, were housed in the hairdryer handle or outside therefrom.

These latter hairdryers, more specifically, conventionally comprised a needle-like electrode, or diffuser, arranged near the hairdryer air outlet, to reduce the distance of the ionizing flow from air.

5

SUMMARY OF THE INVENTION

The aim of the present invention is to provide such a hairdryer-ionizing device assembly specifically designed for overcoming the above mentioned drawbacks of the mentioned prior art.

10

Within the scope of the above mentioned aim, a main object of the invention is to provide a hairdryer, including a ionizing device arranged in a much more efficient manner, both from a functional standpoint and from a size standpoint.

15

Another object of the invention is to provide such a hairdryer-ionizing device assembly which can be made starting from easily available materials and methods.

According to one aspect of the present invention, the above mentioned aim and objects, as well as yet other objects, which will become more apparent hereinafter, are achieved by a hairdryer, including an ionizing device, comprising a box body for holding a suction part, fan means, motor means, heater means, an air flow outlet part, electric switching means and an ion emitting device, constituted by a high voltage, from AC to DC, generator device, electrically coupled to an electrode, characterized in that said high voltage generator device is arranged at an intermediate region between said suction part and said air flow outlet part.

BRIEF DESCRIPTION OF THE DRAWINGS

Further characteristics and advantages of the present invention will become more apparent hereinafter from the following detailed disclosure of a preferred, though not exclusive, embodiment of the invention which is illustrated, by way of an indicative, but not limitative, example in the accompanying drawings, where:

Figure 1 is an exploded side view of the hairdryer including a ionizing device according to the present invention; and

Figure 2 is a perspective view of the hairdryer assembly, comprising a support element and a ionizing high voltage device associated with the hairdryer according to the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference to the number references of the above mentioned figures, the hairdryer-ionizing device assembly according to the present invention comprises a box-like body, including a front shell 1 having an air outlet 10 and a half-handle 12, and a rear shell 2.

The rear shell 2 comprises an air suction inlet 11 and a half-handle 13 which, upon joining the mentioned shells, will provide, together with the front half-handle 12, the handle proper of the hairdryer.

The top portion of the assembled box-like body 1, 2 holds therein a suction part 11, a fan 3,

an electric motor 4, a metal wire resistance 5, mounted about a micanite supporting element, and an air flow outlet 10.

5 The bottom portion of the box-like body, in turn, comprises switch means, optionally mounted on a printed board defined by the assembly 9, provided for mounting thereon diodes or other electronic components.

10 The disclosed assembly is coupled by suitable wiring means, and is connected to the electric power outer net through an electric cable.

According to the invention, the high voltage ion generator ionizing device 7, which is arranged in a single casing, is located between the 15 fan 3 and resistance 5, to allow said ionizing generator to be properly cured by air generated by the mentioned fan.

The ionizing device 7, which has preferably a cylindric shape, is applied to a resistance bearing 20 support element 6, which is clearly shown in figure 2.

Said ionizing device 7 is, advantageously, an easily commercially available miniaturized device, designed for transforming AC current (at 110-220 25 volts) to DC current of high voltage (4-5 kV).

The support element 6, which is preferably made of a plastic material, defines an intermediate element between the electric motor 4 and resistance 5 and is designed for supporting the heater element and 30 said ionizing device 7.

The support element 6 supports, at the bottom thereof, on a side the resistance 5, through a

cross cut or simple cut 16 and, at the other side supporting the electric motor 4 preferably by two pegs.

The support element 6 comprises moreover,
5 at its top portion, a cylindric recess 17, made resilient by a top cut 18, for engaging therein the ionizing device 7.

An electrode or tip 8 is coupled on the heater element 5.

10 Said electrode can also be arranged in a different manner, on the front body or near the air outlet.

With respect to the operation of the hairdryer according to the present invention, the ion
15 emission can be either continuous, as the apparatus operates, or it can occur as hot air or cold air is emitted.

Furthermore, the ion flow can be interrupted by a specifically designed switching
20 means.

It has been found that the invention fully achieves the intended aim and objects.

In fact, the invention provides a hairdryer including a specifically designed supporting element
25 adapted to hold and properly locate therein the ion generating high voltage device, to facilitate hair processing.

In practicing the invention, the used materials, as well as the contingent size and shapes
30 can be any, depending on requirements.